

APPLICATION

Suitable for permanent or semi-permanent use. Can be used indoors and outdoors. Applied by simply bolting onto any of the precut connection holes on any of the 4 sides of a Megadeck stage.

NEEDS ASSESSMENT

- **SPEECH STAGE** - The most common height for a speech stage is 600mm and with the Megadeck step you can simply bolt it on to the stage, ready for use.
- **CURVED INFILLS** - Straight steps can match up to curved Megadeck stages without special curved step infills.
- **STEP INSERTS** - By removing the step inserts, you can add different colours, textures and finishes to your step.
- **STEP FASCIA** - To completely enclose the step, you can choose between a soft or hard finish for the left and right side or just the visible side from an audience perspective.

TECHNICAL DIAGNOSTICS & SPECIFICATIONS

Routed timber top edges ensure a safe and smooth finish. Precut connection points on the step align with the Megadeck stage sections for a variety of positions in the access step can be used in.

The Megadeck step can be used in conjunction with different height stairs to achieve unusual heights, specific to certain venues or applications.

Stage legs with black end caps for protection of flooring.



The mid-size stair in the Megadeck step range is the 600mm step. Perfect for standard stages or use in conjunction with Megadeck stairs for additional height requirements..

FACTS

- Option of **aluminium** or **steel** frame access steps
- **Structural** 15mm timber top
- **Measures** - 1200mm wide x 1200mm deep x 600mm tall
- Weighs **29kg**
- Removable step inserts allow for different fx such as illuminating the stairs with acrylic fonts
- Options of design finishes include; carpet treads, nose edging, non-slip strips
- Locking / Rolling casters can be used to create rolling stairs
- **Australian** made